

Power supply system for work spaces

Trunking 93

raw material colour



Designed to fit in the most demanding architectural and decorative surroundings

- Integration into the surroundings due to the aluminium finishing.
- Free choice of switches and sockets.
- Possibility to attach or flush-mount the trunking on walls and furniture.
- Standard product, immediate availability.

Raw material



Trunking


Fittings, accessories and switches and sockets adapters







Technical characteristics











 $^{^{\}star}$ BS EN 50085-2-1 is the UK implementation of EN 50085-2-1.







Length

2 m

Colour

Aluminium

RAL 9006

Quality marks







Approvals



Bureau Veritas



Ф**3** от 22.07.08 N 123-Ф3 ГОСТ Р 53313-2009 See updated technical information of each part number on www.unex.net

Conformity declaration





Work spaces: office



Health care







Work spaces: office

Work spaces: office





School

Use

Trunking as continuous box

Trunking allows to set the work spaces in any position to facilitate the extension and modification, depending on the user's needs.





Integration of the different types of installations in the same trunking.



Mounting options

On the wall or flush-mounted

Unex trunkings are designed for their mounting on the wall or flush-mounted on brick walls or plaster board, partitions, wooden linings, etc.



Windowsill

Skirting board





Embedded


Attached to the furniture

Safe and easy installation


Wiring accessories

Double-piece adapters:

- Internal piece: for a solid fixing to the base and easy measuring of the cover.
- External and embellishing pieces: hide the cover cut marks.
- IP4X protection against solid foreign objects.








Mounting of switches and sockets

Safe installation

Double-piece adapters:

- Internal piece: for a solid fixing to the base and easy measuring of the cover.
- External and embellishing pieces: hide the cover cut marks.
- IP4X protection against solid foreign objects.



Flexibility to combine a variety of switches and sockets

Unex trunkings are designed to combine different types of installations: electrical, TV, audio-video, sound, data, security, control, etc.

Possibility of extension and evolution of the installations with no dependence on the type of outlet installed.





Flexibility to combine a variety of switches and sockets

Electrical outlets

Universal CEE-7



- Niessen* Olas, Arco, Tacto, Zenit and Stylo.
- BJC*.
- Jung*.
- Simon* 31, 75, 88, 82.
- Mosaic*.
- Bticino*.
- Eunea*.
- Berker*.Gewiss*.

Industrial socket box



- Mennekes*.
- ABL*.
- Simon*.

Modular



- Niessen Zenit*.
- Simon* 27.
- Simon Connect* K45 and compatible.
- Mosaic*.
- Eunea Unica*.
- BJC Sol*.

Modular double



- Mosaic*.
- Simon Connect* K45 "linkable".
- Eunea Unica*.
- Simon CIMA 500*.

Modular triple



- Simon Connect* K45 "linkable".
- Mosaic*.

Universal



- Niessen* Zenit.
- Bticino*.
- Unica-Allegro* (3 modules).
- Gewiss*.

DIN (Bipolar)



- MCB's (Miniature circuit breakers).
- RCD's (Residual current devices).

Data connectors

Flat plate 1 RJ45



Compatible with:

- Systimax solutions.
- Universal type Keystone.

Flat plate 2 RJ45



Compatible with:

- Systimax solutions.
- Universal type Keystone.

Angled plate 2 RJ45



Compatible with:

• Universal type Keystone.

^{*} These brands belong to third parties; they are not related to Unex aparellaje eléctrico, S.L.

Safety

Electrical safety


Protection degree IP4X against solid foreign objects:

The system of adapters for Trunking 93 assures protection degree IP4X or IPXXD against solid foreign objects, acc./EN 50085-2-1.



Resistance to wrenching:

The adapters for power outlets resist 81N, in compliance with EN 50085-1 and European regulations of power outlets.





Safer installations

Trunking 70 mm, bigger bending radius:

- Allows the necessary bending radius for passing the data cables acc./EN 50174-2.
- Larger spare section for cable passing.



Protection of IT cables:

 Data cabling can keep the right bending radius according to EN 50174-2.



Circuit separation:

 Unex 2 lid cover trunking allows to separate cabling and outlets, making unnecessary the use of a socket box for this purpose.





	Trunking sizes (mm)	50x80 50x100		50x150	
	Aluminium RAL 9006 (Part no. 93xxx-03)	50	50	50	
	Cover sizes (mm)	65	80	65 65	
Maxi	imum number of compartments	2	2	4	
Trunking 2 m		93020-03 93021-03 93074-03		93074-03	
Accessories in U23X					
	Divider 2 m	93820			
Fittings in U24X					
	Flat angle	93220-03	93221-03	93224-03	
A B	External angle	93270-03	93271-03	93274-03	
118	Internal angle	93320-03	93321-03	93324-03	
	End cover	93370-03	93371-03	93374-03	
Ti	Joint cover piece	93520-03	93521-03	93524-03	
4	Straight derivation Branching to a 100 mm wide trunking	93421-03			
*	Internal angle derivation Branching to a 100 mm wide trunking	93471-03			
-	L Profile 2 m	93575-03			
	Floor strip 2 m U23X White RAL 9010	93570-2			
	Floor strip (White) external angle RAL 9010	93572-2			



70x100	70x130	70x170		70x170 70x			
70	70	70	170	7	210		
80	80	65	80	80	80		
2	2	4		4			
93031-03	93032-03	93086-03		93087-03			
	99	3830					
93231-03	93232-03	93236-03		93237-03			
93281-03	93282-03	93286-03		93287-03			
93331-03	93332-03	93336-03		93337-03			
93381-03	93382-03	93386-	93386-03		93386-03 93387-0		37-03
93531-03	93532-03	93536-	93536-03		37-03		
	934	l31-03					

93575-2

93580-2

93582-2

See next page 🔱



	Trunking sizes (mm)	50x80	50x100	50x150				
	(Aluminium) RAL 9006 (Part no. 93xxx-03)	50	50	50				
	Cover sizes (mm)	65	80	65 65				
Max	ximum number of compartments	2	2	4				
	Trunking 2 m	93020-03	93021-03	93074-03				
Cable protection elem	nents in U24X							
	Corner-piece flat angle							
	Corner-piece external angle							
	Divider protective piece							
Other accessories in U23X								
	Junction	93550						
Fixing elements in USSX								
	Trunking plug Note: Use drill bit Ø6 mm.							
Adapters for switches	s and sockets in U24X							
	Adapter for switches and sockets	See table of ada						
Modular adaptation of	of the Flexible runway 51 in	U24X (See Furniture su	upply 51)					
	Modular adapter for Flexible runway 51	51623-03	51624-03	51623-03				




70x100	70x130	70x	170	70x2	10		
70	70	170		70	210		
80	80	65	80	80	80		
2	2	2	4	4			
93031-03	93032-03	93086-03		93087	7-03		
	93	B80					
	938	370					
93550							
25106							
See table of adapters, according to the size of the cover. (See pages 126-127).							
	5162	24-03					
<u> </u>							

See next page 🔱





Adapters for Trunking 93 cover 65 mm.



- (1) Compatible with RJ45 Systimax solutions and Universal type Keystone (AMP, Krone, Nexans, Jetlan, Belden, Brand-Rex and OPENETICS). For specific types or brands, please contact us.
- (2) Compatible with RJ45 Universal type Keystone (AMP, Krone, Nexans, Jetlan, Belden, Brand-Rex and OPENETICS). For specific types or brands,
- (3) Most of the switches and sockets of K type are compatible with this adapter. However, there are some part numbers (for example KB076, KB76, K130A, 2u. KA76, 2u. K302 + K115, etc.) that can only be mounted on the double plate 93613-03 or on the triple plate 93618-03 in the central area, placing blind lids on the sides.
- (4) For electrical outlets DIN, the box 93718 is necessary to separate circuits.
- (5) The use of the box is necessary to assure the separation of circuits.


See next page



^{*}These brands belong to third parties, they are not related to Unex aparellaje eléctrico, S.L.



Adapters for Trunking 93 cover 80 mm.



- (1) Frames shall be supplied by the socket manufacturer. We recommend frames with straight corners.
- (2) Box for industrial outlets, compatible with some outlets from Mennekes brand and others. Please contact us for details.
- (3) Compatible with RJ45 Systimax solutions and Universal type Keystone (AMP, Krone, Nexans, Jetlan, Belden, Brand-Rex and OPENETICS). For specific types or brands, please contact us.
- (4) Compatible with RJ45 Universal type Keystone (AMP, Krone, Nexans, Jetlan, Belden, Brand-Rex and OPENETICS). For specific types or brands, please contact us.
- (5) Most of the switches and sockets of K type are compatible with this adapter. However, there are some part numbers (for example KB076, KB76, K130A, 2u. KA76, 2u. K302 + K115, etc.) that can only be mounted on the double plate 93614-03 or on the triple plate 93619-03 in the central area,
- placing blind lids on the sides.
- (6) 1, 2 or 3 outlets of 25 mm. module can be installed. (7) For electrical outlets DIN, the box 93719 is necessary to separate circuits or to fix in trunkings of 70 mm high.
- (8) The use of the box is necessary to assure the separation of circuits.
- (9) Contains a divider part no. 93720 to separate circuits. It can also be sold individually.
- *These brands belong to third parties, without relationship with Unex aparellaje eléctrico, S.L.



Useful cross-sections (mm²)

	Sizes (mm)	50x80	50x100	50x150			
Part no.	Aluminium RAL 9006	93020-03	93021-03	93074-03			
Mounting of switches a	nd socket outlets						
Universal outlets without box			2150				
Modular outlets without box		1565	2140	1425 1425			
Universal or industrial outlets with box			675 675				
Modular and DIN outlets with box		440 440	480 480	425 320 320 425			
Distribution							
Without divider		3110	3890	2955			
With divider		1400 1400	1795 1795	1380 1275 1275 1380			
With divider and corner-piece		1075 1075	1385 1385	1070 985 985 1070			



	70x100	70x130	70x170	70x210				
	93031-03	93032-03	93086-03	93087-03				
				l				
	3855	5920	4335	4265				
	3840	5910	2796	4250				
	3060	5130	4335	3475				
	2625	4695	2350	3035				
	5590	7660	4335	6000				
	2600 2600	3635 3635	2100 1895 2385 2600	2560 2560 2560 3090				
	2165 2165	3025 3025	1750 1565 1970 2150	2570 2100 2100 2570				



www.unex.net


Technical information

You Tube Unex Solutions

- Technical specificationsMounting instructions
- Different database formats



• Mounting videos



COPYRIGHT: All trademarks, brands or distinctive signs, of any kind, that might appear in the present vebsite are the property of Unex aparellaje eléctrico, S.L. or of third parties. The use or access to the present website and/or to its services should not be interpreted, under no circumstances, as conferring any ights to the User on the mentioned trademarks, brands or distinctive signs.	
Furthermore, all Contents are the property of Unex aparellaje eléctrico, S.L. or of third parties. As stated in the mentioned Legal Notice, none of the operation rights existing or that might exist about the mentioned Contents should be understood as transferable to the User, beyond those strictly necessary for the correct use of the Portal and the Services.	

