

Fixing elements


25
26

Fastening system for tubes and
cables

Fastening system for cabinets
and machines

Compatible with Cable ties 22.
Halogen free insulating material.
Fixing elements 26 detectable (blue color).

Product family information



Raw material



Added value



Technical characteristics

OUTDOORS



U63X - Black

INDOORS



U63X - Black
U64X - Grey

TEMPERATURE



Minimum installation
temperature: -15°C
Service temperature:
-40°C to +60°C

CE MARKING



Conformity with standard
EN 62275:2019.


Conformity declaration



Quality Marks



For more detailed
information see
data sheet



Fixing elements 25

26 Fixing elements U60X · Natural - U62X · Blue

Technical characteristics

INDOORS



Indoor installations.

TEMPERATURE



Minimum installation
temperature:
-30°C and +15°C
Service temperature:
-40°C to + 60°C
-40°C to + 85°C
According to specific
part: see data sheet.

CE MARKING



Conformity with standard
EN 62275:2015: detectable
fixing elements.

Conformity declaration




Quality Marks




Only for family 26 in natural
color.

For more detailed
information see
data sheet





Fixing elements 26

Wall plug


	Diameter (mm)	6	8
	Cable tie wall plug (flush) U63X Black	1253 (2)	1251 (1)
	Cable tie wall plug (flush) U64X Gray	1253-3 (2)	1251-3 (1)
	Cable tie surface mount U63X Black	1252 (3)	

Nail mount




	Nail mount U63X Black	25501
	Nail mount U64X Gray	25501-3

Note:
(1) Soft walls: Drill bit Ø7. Hard walls: Drill bit Ø8.
(2) Soft walls: Drill bit Ø5. Hard walls: Drill bit Ø6.
(3) To bolt on M6 or W 1/4 bolt. To screw with Ø 4,5 mm countersunk screws.

Fixings in U60X Natural

	Self-adhesive mount A = 19 mm B = 3 mm	1254 (1)
	A = 30 mm B = 5 mm	1256 (2)
	Screw mount Ø M4	1243
	Angle mount Ø M4 o M5	1257
	Ø 4 to 17 mm Cable clamp	1201
	Ø 15 to 33 mm	1202

Detectable Fixings in U62X Blue

	Screw mount DT Ø M4	1243DT
	Angle mount DT Ø M4 o M5	1257DT
	A = 30 mm B = 5 mm Self-adhesive mount DT	1256DT (2)
	A = 19 mm B = 3 mm	1254DT (1)

Notes
(1) Part no. 1254 / 1254DT is equipped with a hole to assure excellent fixing with a screw M3.
(2) Part no. 1256 / 1256DT is equipped with a hole to assure excellent fixing with a screw M4.

NEW