



Trunking halogen free

93


Power supply system for
work spaces

Flexibility to combine a variety of switches and
sockets.

Independent compartments with fixed divider.

Insulating material: no earthing required nor
equipotential connection.

Product family information



**100% recycled halogen free
thermoplastic component**


U48X 

Added value



Technical characteristics

ELECTRICAL




No earthing required.

SERVICE TEMPERATURE




-25°C / +90°C

MECHANICAL



IK08

PROTECTION DEGREE




IP4X, mounted on the wall.

FIRE



Non flame propagating.

LENGTH



2 m


CONFORMITY DECLARATION



APPROVALS



For more detailed information see data sheet



Quality Marks



EN 50085-2-1:2006 + A1:2011





Work spaces: office



Work spaces: checkpoint



Work spaces: office renovation

	Trunking sizes (mm)	50x80	50x100	50x150
 White	Dimensions (mm)			
	Cover sizes (mm)	65	80	65 65
	Maximum number of compartments	2	2	4
	1 compartment trunking 2 m	93020-42	93021-42	
	2 compartments trunking 2 m			93074-42

Accessories in U43X

	Divider 2 m	93820-40
--	-----------------------	-----------------

Fittings

	Flat angle	93220-42	93221-42	93224-42
	External angle	93270-42	93271-42	93274-42
	Internal angle	93320-42	93321-42	93324-42
	End cover	93370-42	93371-42	93374-42
	Joint cover piece	93520-42	93521-42	93524-42
	Straight derivation Branching to a 100 mm wide trunking	93421-42		

NEW

See next page

	Cover sizes (mm)	65	80
 White	Dimensions (mm)		

Single plate RJ45

	Flat 1RJ45 (8)	93749-42	93750-42
	Flat 2RJ45 (8)	93751-42	93752-42

Single adapter

	Simon 27 (1)	93623-42	93624-42
	Mosaic compatible - Simon K45 - Schneider Unica Ref. NU (1)	93608-42 (2)	93609-42 (3)

Double adapter

	Mosaic compatible - Simon K45 - Schneider Unica Ref. NU (1)	93613-42 (2)	93614-42 (3)
	Universal		93644-42 (5)

Triple adapter

	Mosaic compatible - Simon K45 - Schneider Unica Ref. NU (1) (2)	93618-42 (9)	93619-42 (10)
--	--	---------------------	----------------------

Universal single adapter in U42X (4)

	Universal CEE-7		93604-40
	Universal CEE7 outlet box		93709-40 (6)

Socket boxes in U42X (6)

	Single adapter	93713-40	93714-40
	Double adapter	93718-40	93719-40 (7)

Notes

- (1) These brands belong to third parties; they are not related to Unex aparellaje eléctrico, S.L.
- (2) Most of the switches and sockets of K type are compatible with this adapter. However, there are some part numbers (for example KB076, KB76, K130A, 2u. KA76, 2u. K302 + K115, etc.) that can only be mounted on the double plate 93613-42 or on the triple plate 93618-42 in the central area, placing blind lids on the sides.
- (3) Most of the switches and sockets of K type are compatible with this adapter. However, there are some part numbers (for example KB076, KB76, K130A, 2u. KA76, 2u. K302 + K115, etc.) that can only be mounted on the double plate 93614-42 or on the triple plate 93619-42 in the central area, placing blind lids on the sides.
- (4) Frames shall be supplied by the socket manufacturer. We recommend frames with straight corners.
- (5) 1, 2 or 3 outlets of 25 mm. module can be installed.
- (6) The use of the box is necessary to assure the separation of circuits.
- (7) Contains a divider.
- (8) Compatible with RJ45 Systemax solutions and Universal (CEE) type Keystone (AMP, Krone, Nexans, Jetlan, Belden, Brand-Rex and OPENETICS). For specific types of brands, please contact us.
- (9) For single-circuit installations only: power or signal. If circuit separation is required, the U24X raw material box ref. 93728, with halogens, must be installed.
- (10) For single-circuit installations only: power or signal. If circuit separation is required, the U24X raw material box ref. 93729, with halogens, must be installed.

NEW