



Trunkings for HVAC
U23X · Colour white

30

Installation possibilities of pipes

Installation possibilities of several types of pipes

		Copper tube + insulation thickness 9 mm. or pre-insulated copper tube				
		40x60	40x90	60x60	60x90	60x110
Cooper tubes combinations						
Liquid	Gas	30021-2	30022-2	30031-2	30032-2	30033-2
 1x1	1/4"	3/8"				
	1/4"	1/2"				
	1/4"	5/8"				
	3/8"	5/8"				
	3/8"	3/4"				
 2x1	1/4"	3/8"				
	1/4"	1/2"				
	1/4"	5/8"				
	3/8"	5/8"				
	3/8"	3/4"				
 3x1	1/4"	3/8"				
	1/4"	1/2"				
	1/4"	5/8"				
	3/8"	5/8"				
	3/8"	3/4"				

Pipe pair (liquid-gas)	Waste pipe Ø20 mm.	The pipes insulator must be compressed	Recommended installation	Only for straight sections

NOTE: Trunking part no. 73110-2 (30x40) is suitable to carry waste and cooling pipes separately.

Data contained in this table are merely indicative.

Unex aparellaje eléctrico, S.L. disclaims all responsibility due to the use of this table.

This table results from Unex aparellaje eléctrico, S.L. technical department's research. Its total or partial reproduction without express consent from Unex aparellaje eléctrico, S.L. is forbidden.