

---





















Trunkings for HVAC  
U23X · Colour white

31

---

Installation possibilities of pipes

## Installation possibilities for pipe combinations

Copper pipe + Insulating thickness 10 mm or Pre-insulated copper tube					
	35x35	45x75	60x75	60x100	95x140
<b>Detachable strips</b>		 <b>31021-02 + 31075-04</b>	 <b>31032-02 + 31075-04</b>	 <b>31033-02 + 31100-04</b>	 <b>31045-02 + 31140-04</b>
<b>Single base plates</b>	 <b>31010-02 + 31130-04</b>	 <b>31021-02 + 31175-04</b>	 <b>31032-02 + 31175-04</b>	 <b>31033-02 + 31101-04</b>	
<b>Drain pipe</b>					
<b>1x1</b>					
<b>2x1</b>					
<b>3x1</b>					
<b>4x1</b>					
<b>5x1</b>					
<b>Legend</b>		Drain pipe 20 mm rigid and flexible	Liquid's pipe 1/4" + Insulating thickness 10 mm	Gas' pipe 3/8" + Insulating thickness 10 mm	
					

Note: The information provided in this table is for indicative purposes only.

Unex aparellaje eléctrico, S.L. accepts no responsibility for the use of the table for calculations in connection with the installation.

This table is the result of research by the Unex aparellaje eléctrico, S.L. technical department. Its full or partial reproduction without express authorization by Unex aparellaje eléctrico, S.L. is hereby forbidden.