

---

Kanał grzebieniowy  
U23X · Kolor szary









77









---








Rozmiary przekrojów użytkowych







# Rozmiary przekrojów użytkowych (mm<sup>2</sup>)

Zalecane pojemności na przewody

Rozmiary (mm)		18x20	25x20	33x30	42x20	42x30	42x43	42x60
<b>Nr art.</b>	<b>Szary</b> RAL 7030	<b>18.20.77</b>	<b>25.20.77</b>	<b>30.30.77</b>	<b>40.20.77</b>	<b>40.30.77</b>	<b>40.40.77</b>	<b>40.60.77</b>
		 234	 322	 728	 586	 940	 1460	 2112
Przewody V250 Liczba przewodów (wskaźnik wypełnienia 1,5)*	0,5 mm <sup>2</sup>	43	53	116	96	154	237	346
	0,75 mm <sup>2</sup>	28	35	77	63	102	157	229
Przewody H05/07 V-K Liczba przewodów (wskaźnik wypełnienia 1,5)*	1 mm <sup>2</sup>	18	23	50	41	66	102	150
	1,5 mm <sup>2</sup>	14	17	37	30	49	75	110
	2,5 mm <sup>2</sup>	9	12	26	21	34	52	76

Rozmiary (mm)		60x20	60x30	60x43	60x60	60x80	60x100	60x120
<b>Nr art.</b>	<b>Szary / Niebieski</b> RAL 7030 / RAL 5012	<b>60.20.77</b>	<b>60.30.77</b>	<b>60.40.77</b> <b>776040-06</b>	<b>60.60.77</b> <b>776060-06</b>	<b>60.80.77</b>	<b>60.100.77</b>	<b>60.120.77</b>
		 870	 1387	 2137	 3092	 4225	 5362	 6380
Przewody H05/07 V-K Liczba przewodów (wskaźnik wypełnienia 1,5)*	1 mm <sup>2</sup>	62	98	150	219	299	384	450
	1,5 mm <sup>2</sup>	45	72	111	161	220	283	331
	2,5 mm <sup>2</sup>	32	50	77	112	153	196	230
	4 mm <sup>2</sup>	25	40	61	89	122	157	184
	6 mm <sup>2</sup>	14	23	35	51	70	90	106

Rozmiary (mm)		80x30	80x43	80x60	80x80	80x100	80x120
<b>Nr art.</b>	<b>Szary / Niebieski</b> RAL 7030 / RAL 5012	<b>80.30.77</b> <b>778030-06</b>	<b>80.40.77</b> <b>778040-06</b>	<b>80.60.77</b> <b>778060-06</b>	<b>80.80.77</b> <b>778080-06</b>	<b>80.100.77</b> <b>7780100-06</b>	<b>80.120.77</b> <b>7780120-06</b>
		 1865	 2874	 4128	 5630	 7177	 8572
Przewody H05/07 V-K Liczba przewodów (wskaźnik wypełnienia 1,5)*	1 mm <sup>2</sup>	132	203	291	399	504	606
	1,5 mm <sup>2</sup>	97	149	215	293	371	446
	2,5 mm <sup>2</sup>	68	104	149	204	258	309
	4 mm <sup>2</sup>	54	83	118	162	206	247
	6 mm <sup>2</sup>	31	47	68	92	118	142

Rozmiary (mm)		100x43	100x60	100x80	100x100	100x150
Nr art.	<b>Szary</b> RAL 7030	<b>100.40.77</b>	<b>100.60.77</b>	<b>100.80.77</b>	<b>100.100.77</b>	<b>100.150.77</b>
		 3585	 5179	 7110	 9000	 13450
Przewody H05/07 V-K Liczba przewodów (wskaźnik wypełnienia 1,5)*	1 mm <sup>2</sup>	253	366	502	633	994
	1,5 mm <sup>2</sup>	186	271	369	465	732
	2,5 mm <sup>2</sup>	129	188	257	324	508
	4 mm <sup>2</sup>	103	149	204	258	402
	6 mm <sup>2</sup>	59	85	117	148	201

\* Uwaga! W przypadku innych typów przewodów wymagany przekrój wynika z zastosowania następującego wzoru: Przekrój = przekrój przewodu × liczba przewodów × 1,5.